



BUILDING DIMENSION LEGEND	
I.H.	INTERIOR WALK-IN HEIGHT
B.H.	EXTERIOR BUILDING HEIGHT
O.A.H.	EXTERIOR OVERALL HEIGHT (TO TOP OF REFRIGERATION SYSTEM)
O.A.W.	EXTERIOR OVERALL WIDTH

1. THE I.H., B.H., O.A.H., AND O.A.W. MAY BE ADJUSTED TO MEET SITE CONDITIONS. THE I.H. CAN BE ANY DIMENSION FROM 76" (6'4") "LOW SIDE" - TO 96" (8'0") "HIGH SIDE".
2. SKID HEIGHT IS 1 1/2"
3. B.H. VARIES WITH BUILDING WIDTH (CATHEDRAL ROOF ONLY)
4. SEE CHART BELOW FOR CATHEDRAL ROOF BUILDING HEIGHTS.
5. FLAT ROOF HEIGHTS ARE AS STATED IMMEDIATELY BELOW.
 - a. WALK-IN WIDTHS OF 10' OR LESS HAVE A ROOF THICKNESS OF 6".
 - b. WALK-IN WIDTHS OVER 10' HAVE A ROOF THICKNESS OF 5 1/2".
6. *SEE AE103D FOR STANDARD REFRIGERATION HEIGHTS, TO FIGURE O.A.H.,

BUILDING WIDTH	6'	7'	8'	9'	10'	11'	12'	13'	14'
FLOOR STRUCTURE									
STANDARD (5.5")	14.5"	15"	15.5"	16"	16.5"	16.5"	17"	17.5"	18"
SKIDS REMOVED (4")	13"	13.5"	14"	14.5"	15"	15"	15.5"	16"	16.5"
FLOORLESS (0")	9"	9.5"	10"	10.5"	11"	11"	11.5"	12"	12.5"



INTERNATIONAL COLD STORAGE
 215 E. 13TH STREET, P.O. BOX 425
 ANDOVER, KS. 67002

800-835-0001
 FAX 316-733-2434

WALK-IN BUILDING AND OVERALL HEIGHTS
 DADE COUNTY ROOF COMPLIANCE

Visit us on the web at, www.icsco.com

DRAWING	DATE	SCALE	REVISED
AE103C	2/10/00	NONE	