


EXTERIOR BASE TRIM



MATERIAL:
 .032 ALUMINUM PAINTED
 TO MATCH BUILDING COLOR

EXTERIOR TRIM KIT:	QUANTITY
EXTERIOR BASE TRIM	10 FEET
#6x1/2" PHILLIPS HEAD TEK SCREW	10 EACH
SILICONE SEALANT	1 TUBE
INSTRUCTIONS	1 TOTAL

INSTALLATION INSTRUCTIONS:

INSTALL EXTERIOR BASE TRIM AS SHOWN. FASTEN TO EXTERIOR WALL AROUND BOTTOM OF BUILDING WITH THE #6x1/2" PHILLIPS HEAD TEK SCREWS PROVIDED. MAXIMUM SCREW SPACING 24". TRIM SHOULD FIT TIGHTLY AND UNIFORMLY AGAINST BUILDING AND CONCRETE PAD. SEAL TOP EDGE OF TRIM WITH THE SILICONE SEALANT PROVIDED. SEALANT SHOULD BE APPLIED IN A UNIFORM, CONTINUOUS, AND SMOOTHED OUT BEAD FOR A NEAT APPEARANCE.



INTERNATIONAL COLD STORAGE
 215 E. 13TH STREET, P.O. BOX 425
 ANDOVER, KS. 67002

800-835-0001
 FAX 316-733-2434

BASE TRIM DETAILS

DRAWING	DATE	SCALE	REVISED
AE123	2/10/00	NONE	